



YIWU HUIZHI TRADING CO., LTD

ADD: 3RD FLOOR, NO.491 NORTH CHOUZHOU ROAD, CHOUCHENG STREET,
YIWU ZHEJIANG PROVINCE, CHINA

MOB: +86 198 6610 5681

TEL: +86 (0579) 8514 3833

E-MAIL: mag@yw-huizhi.com

WEB: <https://yw-huizhi.com/>

Technical Data Sheet

Lubricant H37P

Overview

The lubricant H37P produced by our company is suitable for the production and processing of PVC products.

Application

This product is a polyethylene wax lubricant, which is suitable for the processing and production of PVC products. This product can improve the lubricity and release of polyvinyl chloride, and it has good anti-precipitation property, especially suitable for high-filled rigid PVC products and foamed PVC products; when added to high-filled PVC materials, it can improve the filling rate and maintain good plasticizing performance at the same time. The addition of this product to the foamed PVC material can improve the foaming stability and discharge uniformity, reduce the number of mold dismantling, and prolong the production cycle.

Appearance

White particles or powder

Specification

Item	Index	Unit
Heating Reduction (105℃)	≤1	%
Melting process	95-115	℃

Application Parameters

Suggested Dosage	0.2-1.0	%
------------------	---------	---

Health Performance

Satisfy the specific requirements of ROHS.

Remark

Should be transported in accordance with regulations of non-dangerous goods and stored in a ventilated and dry warehouse.

Package

Packed in kraft paper bags, net weight 25KG.