



YIWU HUIZHI TRADING CO., LTD

ADD: 3RD FLOOR, NO.491 NORTH CHOUZHOU ROAD, CHOUCHENG STREET,
YIWU ZHEJIANG PROVINCE, CHINA

MOB: +86 198 6610 5681

TEL: +86 (0579) 8514 3833

E-MAIL: mag@yw-huizhi.com

WEB: <https://yw-huizhi.com/>

Technical Data Sheet

Processing aids K138T

Overview The acrylic processing aid K138T produced by our company is suitable for the production and processing of PVC rigid foam products.

Application This product exhibits a relatively balanced plasticizing and homogenizing effect, effectively enhancing the dispersion of PVC dry powder in the extruder and overall improving the physical-mechanical properties and surface brightness of PVC extruded products. For PVC rigid foam products, it can significantly enhance the fineness and uniformity of foam cell structures. This product is particularly suitable for the production and processing of PVC wood-plastic foam building materials, PVC rigid profiles, PVC advertising boards, decorative panels, wall panels, WPC flooring, as well as PVC foam products such as air windows and blinds.

Appearance Whiter powder

Specification	Item	Index	Unit
	Heating Reduction	≤1.5	%
	Apparent density	0.3-0.6	g/ml ³
	Intrinsic viscosity	14-16	dL/g

Application Parameters Suggested Dosage 0.5-3.0 %

Health Performance Satisfy the specific requirements of ROHS.

Remark Should be transported in accordance with regulations of non-dangerous goods and stored in a ventilated and dry warehouse.

Package Packaged in PE woven bags, with a net weight of 25KG per bag.