



YIWU HUIZHI TRADING CO., LTD

ADD: 3RD FLOOR, NO.491 NORTH CHOUZHOU ROAD, CHOUCHENG STREET,
YIWU ZHEJIANG PROVINCE, CHINA

MOB: +86 198 6610 5681

TEL: +86 (0579) 8514 3833

E-MAIL: mag@yw-huizhi.com

WEB: <https://yw-huizhi.com/>

Technical Data Sheet

Processing aids K230T

Overview The acrylic processing aid K230T produced by our company is suitable for the production and processing of PVC high filling products.

Application This product has a significant plasticizing promoting effect, which can effectively improve the plasticization and production flowability of PVC dry powder in the extruder, and significantly enhance the physical and mechanical properties and surface smoothness of PVC high filling products; This product is suitable for the production and processing of PVC wood plastic foam building materials, PVC hard profiles, PVC advertising boards, decorative boards, wall panels, WPC flooring and other products, especially for the production and processing of PVC high filling products.

Appearance Whiter powder

Specification	Item	Index	Unit
	Heating Reduction	≤1.5	%
	Apparent density	0.35-0.55	g/ml ³
	Intrinsic viscosity	14.5-15.5	dL/g

Application Parameters Suggested Dosage 0.5-3.0 %

Health Performance Satisfy the specific requirements of ROHS.

Remark Should be transported in accordance with regulations of non-dangerous goods and stored in a ventilated and dry warehouse.

Package Packed in woven bags with net weight of 25KG per bag.