YIWU HUIZHI TRADING CO., LTD

ADD: 3RD FLOOR, NO.491 NORTH CHOUZHOU ROAD, CHOUCHENG STREET, YIWU ZHEJIANG PROVINCE, CHINA

MOB: +86 198 6610 5681 TEL: +86 (0579) 8514 3833

E-MAIL: mag@yw-huizhi.com WEB: https://yw-huizhi.com/

Technical Data Sheet

Stabilizer CZ3366L

Overview	The environmentally friendly calcium zinc stabilizer CZ3366L produced by our company is suitable for the production and processing of ABA co extruded flooring, carbon crystal board, WPC flooring, crash board and other products.		
Application	CZ3366L calcium zinc stabilizer is suitable for processing ABA co extruded flooring, carbon crystal board, WPC flooring, anti-collision board and other products. This product has balanced thermal stability, which can ensure consistent thermal stability of the surface, core, and bottom layers during co extrusion, avoiding problems such as uneven thermal decomposition and color difference. Assist in achieving uniform wall thickness and precise size of the product, effectively enhancing interlayer bonding and preventing delamination. The product has excellent comprehensive performance, good production stability, smooth surface, and a wide range of applications.		
Appearance	White microbeads or powder		
Specification	Item	Index	Unit
	Heating reduction:	≤2.0	%
	Initial melting point:	≥65	℃
	Processing temperature:	150-200	℃
Application Parameters	Suggested Dosage:	1.0-1.5	% (Calculated per 25kg resin)
Health Performance	Satisfy the specific requirements of ROHS.		
Remark	Should be transported in accordance with regulations of non-dangerous goods and stored in a ventilated and dry warehouse.		
Package	Packaged in PE woven bags, with a net weight of 25KG per bag.		